Patent claims

1. Direct synthesis process for preparing etherified melamine resin condensates with average molecular weights of from 500 to 50 000, the melamine resin condensates are free from hydroxymethyleneamino groups bonded to the triazine rings of the melamine resin condensate and from  $-NH-CH_2-O-CH_2-NH-$  groups linking triazine rings

10

## characterized in that

- a) in the first step of the reaction, an etherified melamine resin precondensate is prepared in alcoholic
   solution,
- b) in at least one vaporization step, the concentration of the etherified melamine resin precondensate in alcoholic solution is increased, C<sub>4</sub>-C<sub>18</sub> alcohols, diols
   20 of the type represented by HO-R-OH and/or tetrahydric alcohols based on erythritol being added to the melamine resin precondensate prior to, during and/or after the concentration-increase process,
- 25 c) in a second step of the reaction, the increased-concentration melamine resin precondensate is reacted, using a mixer, in particular a kneader.
- Direct synthesis process according to Claim 1,
   characterized in that, after the second step of the reaction, the etherified melamine resin condensate is discharged and pelletized.
- Direct synthesis process according to Claim 1 or
   characterized in that the alcohol in the first step of the reaction is methanol.
  - 4. Direct synthesis process according to at least one of the preceding claims, characterized in that, in

the first step of the reaction, the methylolation of the melamine takes place with subsequent etherification.

5. Direct synthesis process according to at least one of the preceding claims, characterized in that, in the first step of the process, formaldehyde is used in the form of formalin solution at variable concentration and/or paraformaldehyde.

10

6. Direct synthesis process according to Claim 4, characterized in that the methylolation takes place at a pH of from 7 to 9 and the etherification takes place at a pH of from 5.5 to 6.5.

15

7. Direct synthesis process according to at least one of Claims 1 to 4, characterized in that, in the first step of the reaction, the methylolation and the etherification take place simultaneously.

20

- 8. Direct synthesis process according to Claim 7, characterized in that the first step of the reaction takes place at a pH of from 5.5 to 6.5.
- 9. Direct synthesis process according to at least one of the preceding claims, characterized in that the first step of the reaction takes place in the presence of acidic, or of a mixture of acidic and basic, ion exchangers.

30

10. Direct synthesis process according to at least one of the preceding claims, characterized in that, in the first step of the reaction, a reaction temperature of from 70 to 160°C, in particular from 95 to 100°C, is

35 established.

11. Direct synthesis process according to at least one of the preceding claims, characterized in that the

first step of the reaction is carried out using a melamine/formaldehyde molar ratio

## of from 1: 2.0 to 1: 4.0.

- 12. Direct synthesis process according to at least one of the preceding claims, characterized in that the increased-concentration melamine resin precondensate obtained after the vaporization process has a concentration of from 95 to 99% by weight.
- 13. Direct synthesis process according to at least one 10 of the preceding claims, characterized in that the vaporization of the low-molecular-weight components takes place in two stages.
- 14. Direct synthesis process according to at least one of the preceding claims, characterized in that use is made of at least one diol represented by the type HO-R-OH with molecular weight of from 62 to 20 000 or of a mixture of at least two diols represented by the type HO-R-OH with molecular weights of from 62 to 20 000,
- 20 where the substituent R may have one of the following structures

```
C_{2}-C_{18}-alkylene,
-CH(CH_{3})-CH_{2}-O-(C_{2}-C_{12})-alkylene-O-CH_{2}-CH(CH_{3})-,
-CH(CH_{3})-CH_{2}-O-(C_{2}-C_{12})-arylene-O-CH_{2}-CH(CH_{3})-,
-(CH_{2}-CH_{2}-CH_{2}-CH_{2}-CH_{2}-CO-)_{x}-(CH_{2}-CHR)_{y}-
-[CH_{2}-CH_{2}-O-CH_{2}-CH_{2}]_{n}-,
-[CH_{2}-CH(CH_{3})-O-CH_{2}-CH(CH_{3})]_{n}-,
-[CH_{2}-CH(CH_{3})-O-CH_{2}-CH(CH_{3})]_{n}-,
-[(CH_{2}-CH_{2}-CH_{2}-CH_{2}-CH_{2}-I)_{n}-,
-[(CH_{2})_{2-8}-O-CO-(C_{6}-C_{14})-arylene-CO-O-(CH_{2})_{2-8}-I)_{n}-,
-[(CH_{2})_{2-8}-O-CO-(C_{2}-C_{12})-alkylene-CO-O-(CH_{2})_{2-8}-I)_{n}-,
where n = 1 - 200; x = 5 - 15;
```

sequences which contain siloxane groups and are represented by the type

polyester sequences which contain siloxane groups and are represented by the type

$$-[(X)_r-O-CO-(Y)_s-CO-O-(X)_r]-,$$

10 where

15

5

$$C_{1}-C_{4}-alkyl \quad C_{1}-C_{4}-alkyl \\ | \quad | \quad | \\ Y = -\{(C_{6}-C_{14})-arylene-CO-O-(\{Si-O-[Si-O]_{y}-CO-(C_{6}-C_{14})arylene-\} \\ | \quad | \quad | \\ C_{1}-C_{4}-alkyl \quad C_{1}-C_{4}-alkyl$$

or

20

where r = 1 - 70; s = 1 - 70 and y = 3 - 50;

polyether sequences which contain siloxane groups and are represented by the type

5 where  $R'_2 = H$ ;  $C_1-C_4$ -alkyl and y = 3 - 50;

sequences based on alkylene oxide adducts of melamine and represented by the type of

2-amino-4,6-di- $(C_2-C_4)$  alkyleneamino-1,3,5-triazine sequences

phenol ether sequences based on dihydric phenols and on  $\text{C}_2\text{--}\text{C}_8$  diols and represented by the type of

-  $(C_2-C_8)$  alkylene-O- $(C_6-C_{18})$  -arylene-O- $(C_2-C_8)$  - 15 alkylene sequences.

20

- 15. Direct synthesis process according to at least one of the preceding claims, characterized in that the etherified melamine resin condensates are mixtures with average molecular weights of from 500 to 2500 composed of tris(methoxymethylamino)triazine and its higher-molecular-weight oligomers.
- Direct synthesis process according to at least one 25 of the preceding claims, characterized in that, prior to and/or during the concentration-increase process, i.e. prior to the first and/or prior to the second stage and/or after the concentrationvaporizing increase process, i.e. prior to the second step of the reaction, anhydrides and/or acids dissolved in alcohols 30 or in water added to are the melamine resin precondensate.

17. Direct synthesis process according to at least one of the preceding claims, characterized in that the kneader is a continuously operating, at least to some extent self-cleaning, extruder with vacuum venting.

5

18. Direct synthesis process according to at least one of the preceding claims, characterized in that the kneader used comprises a twin-screw extruder with vent zones.

10

- 19. Direct synthesis process according to at least one of the preceding claims, characterized in that, in the continuous kneader, up to 75% by weight of fillers and/or reinforcing fibres, other reactive polymers of the type represented by ethylene copolymers, maleic 15 anhydride copolymers, modified maleic anhydride copolymers, poly(meth)acrylates, polyamides, polyesters and/or polyurethanes are also incorporated, as are up to 2% by weight of stabilizers, UV absorbers and/or auxiliaries, each weight being based on the etherified 20 melamine resin condensates.
- 20. Direct synthesis process according to at least one of the preceding claims, characterized in that the 25 first step of the reaction is executed in a stirred tank or in a continuous reactor.
- 21. Direct synthesis process according to at least one of the preceding claims, characterized in that the process is carried out either continuously or batchwise.
- 22. Direct synthesis process according to at least one of the preceding claims, characterized in that the 35 melamine resin condensates are free from hydroxymethyleneamino groups bonded to the triazine rings of the melamine resin condensate

and from  $-NH-CH_2-O-CH_2-NH-$  groups linking triazine rings.

- 23. Use of etherified melamine resin condensates prepared by a direct synthesis process according to at least one of Claims 1 to 22 for processing in the melt, in particular in the form of hot-melt adhesives and for producing sheets, pipes, profiles, injection mouldings, fibres, coatings and foams, or for processing from solution or dispersion in the form of an adhesive, impregnating resin, surface-coating resin or laminating resin or for producing foams, microcapsules or fibres.
- 24. Melamine resin products, produced via a melamine 15 resin condensate etherified using a direct synthesis process according to at least one of Claims 1 to 22.